



Solid

Product #600

**Longest Lasting Wood Stain & Sealer
Technical Data Sheet**

Makes Old Wood Look New!

10 Year Warranty

100% Acrylic Stain and Sealant in One

UV Resistant

Mildew Resistant

Ultimate Waterproofing Protection

Fade and Wear Resistant

Environmentally Friendly

Self Priming

WOOD Rx Solid is a 100% acrylic solid color wood stain designed to effectively seal, protect and beautify wood and composite surfaces. Its specialized formula resists moisture penetration, mildew, water staining and uneven discoloration. **WOOD Rx Solid** is designed for maximum performance in any climate. **WOOD Rx Solid** is available in any color and produces a finish which is durable and easy to maintain. **WOOD Rx Solid** is the best prescription for solid wood protection.

RECOMMENDED USES:

For use on virtually all properly prepared, exterior wood surfaces such as decks, docks, sidings, specialty hardwoods, pressure treated lumber, garden furniture, playhouses, composite decking, siding and log/timber frame homes. Contact an INSECO representative for detailed specifications.

SURFACE PREPARATION:

Dirt, grease, grime and any foreign material should be removed before applying **WOOD Rx Solid**. Be sure surface is clean and dry.

1. Apply a solution of 1 part household bleach or bleach alternative, 1 part dishwashing soap and 4 parts water.
2. Scrub and/or pressure wash as necessary to remove any surface contaminants.
3. Apply a test sample of **WOOD Rx Solid** to insure proper adhesion and an appealing appearance. If beading or crawling occurs, contact INSECO prior to applying.

*****Note: When applying a solid wood stain to new or uncoated wood, there is a possibility that tannin stains may appear. Certain wood types and colors may be more susceptible to tannin stains than others. Please contact INSECO to learn more regarding tannin staining and how to prevent or minimize it.**

APPLICATION:

1. Stir **WOOD Rx Solid** thoroughly before use.

2. Apply with a brush, roller or airless sprayer
3. Apply 1-2 coats as required to achieve a uniform appearance. Two coats are recommended for maximum performance. Allow 2-4 hours between coats.
6. **WOOD Rx Solid** may be applied to damp or dry wood.

Do not apply if the threat of rain exists. Keep from freezing. Do not use if temperature is below 50 degrees F.

RECOMMENDED THINNER:

WOOD Rx Solid does not require thinning and should be used as is, directly from the container.

TECHNICAL DATA:

Finish: Satin

Pigment: Type: Titanium Dioxide & Inert Pigments

Vehicle Type: 100% Acrylic

Solvent Type: Water

% Solids By Weight: 49% +/- 2%

% Solids By Volume: 35% +/- 2%

Density: 10.72 lbs. Per gallon

Viscosity @ 75 deg. F (24 deg. C): 105 +/- 2 K.U.

V.O.C.: Less than 150 g/l

Estimated Dry Time: Touch 30-60 minutes. Recoat 2-4 hours. Foot traffic 24 hours.

Flash Point, Minimum: Not Flammable

Flame Spread: Class A rating on non-combustible substratum

Clean Up:

Clean up drips and spills immediately using a damp cloth. Clean tools and equipment with soap and fresh water.

Coverage (Theoretical): Coverage will depend on porosity and contour of the surface being coated. Coverage typically averages 250-350 square feet per gallon. Two coats are always recommended for maximum performance.

RESISTANCE TO:

Weather/UV :Excellent

Moisture Penetration :Excellent

Peeling/Flaking/Blistering :Excellent

Mildew :Excellent

CAUTION: KEEP OUT OF REACH OF CHILDREN!

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear an NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Technical data contained herein is true and accurate at the date of issue, but is subject to change without notice. An INSECO representative should be contacted with any questions concerning product information or application procedures. Our products conform to INSECO quality standards, but no other warranty is expressed or implied. Liability, if any, is limited to the replacement of product or purchase price.

02/02/09

INSECO, Inc.
5601 Banner Drive
Ft. Myers, FL 33912
800-883-5150
www.woodrx.com