



Original Formula

Product #610

Longest Lasting Wood Stain & Sealer Technical Data Sheet

WOOD Rx is, by far, the best prescription for any wood surface. It is a technologically advanced, water based finish that effectively penetrates, seals and protects exterior wood surfaces. WOOD Rx resists moisture penetration and retards the aging (silvering) process of new wood. It contains an effective fungicide which resists mildew growth on the film and a powerful UV screener which filters out the sun's harmful rays. WOOD Rx protects and beautifies wood surfaces 3-5 times longer than conventional, competitive wood sealers. **WOOD Rx** original is available in an array of transparent and semi-transparent.

RECOMMENDED USES:

For use on virtually all properly prepared, exterior wood surfaces such as decks, docks, sidings, specialty hardwoods, pressure treated lumber, garden furniture, playhouses and log/timber frame homes. Contact an INSECO representative for detailed specifications.

SURFACE PREPARATION:

Dirt, grease, grime and any foreign material should be removed before applying **WOOD Rx**. Be sure surface is clean and dry.

1. Apply a solution of 1 part household bleach or bleach alternative, 1 part dishwashing soap and 4 parts water.
2. Scrub and/or pressure wash as necessary to remove any surface contaminants.
3. Apply a test sample of **WOOD Rx** to insure proper adhesion and an appealing appearance. If beading or crawling occurs, contact INSECO prior to applying.

APPLICATION:

1. Stir **WOOD Rx** thoroughly before use.
2. Apply with a brush, roller or airless sprayer
3. Two thin coats are recommended for maximum performance. The second coat may be applied as soon as the first coat is dry to the touch. The surface must be dry to apply the second coat.
3. Do not apply in direct, hot sunlight or when surface temperatures are below 50 deg. F. If surface is hot and dry, cool down with clean, fresh water and apply **WOOD Rx** to cool, moist surface. Avoid runs on vertical surfaces and puddles on horizontal surfaces. Take care to avoid "lapping." Always work with a wet edge and with the grain of the wood. Do not stop in the middle of a board and try to come back later to pick up where you left off. Stop at a logical break point to avoid the possibility of creating lap marks.

Do not apply if the threat of rain exists. Keep from freezing.

NEW PRESSURE TREATED LUMBER:

It is recommended that new pressure treated lumber weather for six months prior to applying **WOOD Rx Original**.

RECOMMENDED THINNER:

WOOD Rx Original does not require thinning and should be used as is, directly from the container.

TECHNICAL DATA:

Finish: Satin

Vehicle Type: 100% Acrylic

Solvent Type: Water

% Solids By Weight: 20% +/- 2%

% Solids By Volume: 19% +/- 2%

Density: 8.60 lbs. Per gallon

Viscosity @ 75 deg. F (24 deg. C): 65-75 K.U.

V.O.C.: Less than 150 g/l

Estimated Dry Time: Touch 30 minutes. Recoat 2-4 hours. Foot traffic 24 hours.

Flash Point, Minimum: Not Flammable

Flame Spread: Class A rating on non-combustible substratum

Clean Up:

Clean up drips and spills immediately using a damp cloth. Clean tools and equipment with soap and fresh water.

Coverage (Theoretical): Coverage will depend on porosity and contour of the surface being coated. Coverage typically averages 250-350 square feet per gallon. Two coats are always recommended for maximum performance.

RESISTANCE TO:

Weather/UV	:Excellent
Moisture Penetration	:Excellent
Peeling/Flaking/Blistering	:Excellent
Mildew	:Excellent

CAUTION: KEEP OUT OF REACH OF CHILDREN!

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear an NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Technical data contained herein is true and accurate at the date of issue, but is subject to change without notice. An INSECO representative should be contacted with any questions concerning product information or application procedures. Our products conform to INSECO quality standards, but no other warranty is expressed or implied. Liability, if any, is limited to the replacement of product or purchase price.

02/02/09

INSECO, Inc.
5601 Banner Drive
Ft. Myers, FL 33912
800-883-5150
www.woodrx.com