



Clear Water Repellent

Longest Lasting Wood Sealer & Water Repellent

Product #670

Technical Data Sheet

WOOD Rx Clear Water Repellent is a water based, non-yellowing, water repellent designed to penetrate, seal and protect exterior wood surfaces from water damage. **WOOD Rx Clear Water Repellent** employs silicone technology which produces long lasting water repellency and it also contains an increased level of fungicide which resists mildew growth in the harshest climates.

RECOMMENDED USES:

For use on virtually all exterior wood surfaces such as decks, docks, sidings, specialty hardwoods, pressure treated lumber, garden furniture, playhouses and log/timber frame homes. Do not apply over previously painted or stained wood surfaces without proper preparation. Contact an INSECO representative for detailed specifications.

SURFACE PREPARATION:

1. Apply a solution of 1 part household bleach or bleach alternative, 1 part dishwashing soap and 4 parts water.
2. Scrub and/or pressure wash as necessary to remove any surface contaminants.
3. Apply a test sample of WOOD Rx to insure proper adhesion. If beading or crawling occurs, contact INSECO prior to applying.

APPLICATION:

1. Stir thoroughly before use.
2. Apply with a brush, roller, foam pad, pump garden sprayer or airless sprayer
3. Saturate the entire surface but avoid puddling.
4. Apply 1-2 coats as required. Two coats are recommended for maximum performance. Allow 1-2 hours between coats.
6. **WOOD Rx Clear Water Repellent may** be applied to damp or dry wood.

Do not apply if the threat of rain exists. Keep from freezing. Do not apply if temperature is below 40 degrees F.

RECOMMENDED THINNER:

WOOD Rx *ultra* does not require thinning and should be used as is, directly from the container.

TECHNICAL DATA:

Finish: Matte

Vehicle Type: Silicone Modified Acrylic

Solvent Type: Water

% Solids By Weight: 19% +/- 2%

% Solids By Volume: 17% +/- 2%

Density: 8.4 lbs. Per gallon

Viscosity @ 75 deg. F (24 deg. C): Waterlike

V.O.C.: Less than 50 g/l

Estimated Dry Time: Touch 30 minutes. Recoat 1-2 hours. Foot traffic 12 hours.

Flash Point, Minimum: Not Flammable

Flame Spread: Class A rating on non-combustible substratum

Clean Up:

Clean up drips and spills immediately using a damp cloth. Clean tools and equipment with soap and fresh water.

Recommended Dry Film Thickness Per Coat: *WOOD Rx Clear Water Repellent* is designed to penetrate and seal.

Coverage (Theoretical): Coverage will depend on porosity and contour of the surface being coated. Coverage typically averages 400 square feet per gallon. Two coats are always recommended for maximum performance.

RESISTANCE TO:

Moisture Penetration :Excellent

Peeling/Flaking/Blistering :Excellent

Mildew :Excellent

CAUTION: KEEP OUT OF REACH OF CHILDREN!

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear an NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Technical data contained herein is true and accurate at the date of issue, but is subject to change without notice. An INSECO representative should be contacted with any questions concerning product information or application procedures. Our products conform to INSECO quality standards, but no other warranty is expressed or implied. Liability, if any, is limited to the replacement of product or purchase price.

02/02/09

INSECO, Inc.
5601 Banner Drive
Ft. Myers, FL 33912
800-883-5150
www.woodrx.com