

DECK Rx

Resurfaces Old Wood & Concrete

*Creates A Smooth, Slip Resistant Finish
Covers Splinters & Small Cracks*

*Easy to Apply
May be Applied to Damp Wood and/or Concrete
Resists Cracking & Peeling
Durable, Mildew & UV Resistant Finish
Fade & Wear Resistant
Environmentally Friendly
Self Priming
10 Year Warranty*

**Product #650
Technical Data Sheet**

DECK Rx is a 100% acrylic finish designed to resurface old wood and concrete. **Deck Rx** covers splinters, fills small cracks and creates a durable, smooth, slip resistant finish. **DECK Rx** will seal, protect and beautify wood and concrete surfaces. **DECK Rx** is designed for maximum performance in any climate. **DECK Rx** is available in any color and produces a finish which is durable and easy to maintain. **DECK Rx** is the best prescription for old wood & concrete protection.

RECOMMENDED USES:

For use on virtually all properly prepared, wood and concrete surfaces such as decks, docks, patios, walkways, benches, railings and walls. For use on both vertical and horizontal surfaces. Not recommended for use where exposed to vehicular traffic. Contact an INSECO representative for detailed specifications.

SURFACE PREPARATION:

Dirt, grease, grime and any foreign material should be removed before applying **DECK Rx**. Be sure surface is clean and dry.

1. Apply a solution of 1 part household bleach or bleach alternative, 1 part dishwashing soap and 4 parts water.
2. Scrub and/or pressure wash as necessary to remove any surface contaminants.
3. Apply a test sample of **DECK Rx** to insure proper adhesion and an appealing appearance. If beading or crawling occurs, contact INSECO prior to applying.

APPLICATION:

1. Stir **DECK Rx** thoroughly before use.
2. Apply with a brush or roller
3. 2 Coats are required to achieve. Allow 2-4 hours between coats.
6. **DECK Rx** may be applied to damp or dry wood and concrete.

Do not apply if the threat of rain exists. Keep from freezing. Do not use if temperature is below 50 degrees F.

RECOMMENDED THINNER:

DECK Rx does not require thinning and should be used as is, directly from the container.

TECHNICAL DATA:

Finish: Satin

Pigment: Type: Titanium Dioxide & Inert Pigments

Vehicle Type: 100% Acrylic

Solvent Type: Water

% Solids By Weight: 49% +/- 2%

% Solids By Volume: 35% +/- 2%

Density: 12.79 lbs. Per gallon

Viscosity @ 75 deg. F (24 deg. C): 120 +/- 2 K.U.

V.O.C.: Less than 150 g/l

Estimated Dry Time: Touch 30-60 minutes. Recoat 2-4 hours. Foot traffic 24 hours.

Flash Point, Minimum: Not Flammable

Flame Spread: Class A rating on non-combustible substratum

Clean Up:

Clean up drips and spills immediately using a damp cloth. Clean tools and equipment with soap and fresh water.

Coverage (Theoretical): Coverage will depend on porosity and contour of the surface being coated. Coverage typically averages 100-150 square feet per gallon. Two coats are always recommended for maximum performance.

CAUTION: KEEP OUT OF REACH OF CHILDREN!

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear an NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Technical data contained herein is true and accurate at the date of issue, but is subject to change without notice. An INSECO representative should be contacted with any questions concerning product information or application procedures. Our products conform to INSECO quality standards, but no other warranty is expressed or implied. Liability, if any, is limited to the replacement of product or purchase price.

02/02/09
800-883-5150
www.woodrx.com